

MATERIAL SAFETY DATA SHEET

1. PRODUCT IDENTIFICATION:

TRADE NAME: **RUBBER DRESSING** or **PRESERVER** or **RD6**

MANUFACTURE'S NAME & ADDRESS: **ALLBRITE CAR CARE PRODUCTS**
4530 E. Eisenhower Circle
ANAHEIM, CA 92807
800-729-9960

DATE PREPARED OR REVISED: 07-5-95

2. HAZARDOUS INGREDIENTS:

Chemical Name	CAS numbers	Percent	Exposure Limits in Air
HAZARD			ACGIH TLV

Paraffinic Petroleum Solvent

*Paraffinic solvent is not hazardous as defined in 29 CFR 1910.1200

3. PHYSICAL PROPERTIES:

Vapor Density (air=1.0)	: Heavier than air
Specific Gravity (Water=1.0)	: < 1.0
Solubility in Water	: Insoluble
Vapor Pressure, mmHg @ 20 C	: < 0.0 at 100 F
Appearance and Odor Name	: Characteristic to Fragrance
Freezing Point or Range	: < 32 F
Boiling Point or Range	: > 500 F
Evaporation Rate (Butyl Acetate=1.0)	: < 1.0
% Volatile By Volume	: Unknown

4. FIRE AND EXPLOSION:

Flash Point (give method)	: > 200 F Tag Closed Cup
Auto Ignition Temperature	: > 500 F
Flammable Limits in Air, Vol %	: lower (LEL) 0.6 upper (UEL) 7.0
Fire Extinguishing Materials:	Water Spray__X__, Foam__X__,

Carbon Dioxide__X__, Dry Chemical__X__, Other____
Specific Fire Fighting Procedures: Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Avoid spraying water directly into storage containers due to danger of boilover.

Unusual Fire and Explosion Hazards: None Known.

5. HEALTH HAZARD INFORMATION:

SYMPTOMS OF OVEREXPOSURE for each Potential Rout of Exposure:

Inhaled: High vapor concentrations are irritating to the eyes and respiratory tract; May cause headaches and dizziness, are anesthetic and may have other central nervous system effects.

Contact With Skin or Eyes: Slightly irritating to eyes but does not injure eye tissue. Low order of toxicity. Frequent or prolonged exposure to skin may irritate and cause dermatitis.

Swallowed: Minimal toxicity. Small amounts of the liquid aspirated into respiratory system during ingestion, or from vomiting, may cause bronchiopneumonia or pulmonary edema.

FIRST AID: EMERGENCY PROCEDURES

Eye Contact: Flush eyes with large amount of water until irritation subsides. If irritation persists, get medical attention.

Skin Contact: Flush with large amount of water and use soap. Remove grossly contaminated clothing, including shoes, and launder before reuse.

Inhaled: Using proper respiratory protection immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. and get prompt medical attention.

Swallowed: If swallowed, DO NOT induce vomiting. Keep at rest and get prompt medical attention.

SUSPECTED CANCER AGENTS?

__X__NO: This product's ingredients are not found in lists below.

YES: Federal OSHA_____, NTP_____, IARC_____.

California employers using Cal/OSHA regulated carcinogens must register with Cal/OSHA. The Cal/OSHA and Federal OSHA carcinogen lists are similar.

6. REACTIVITY DATA:

Stability: Stable Unstable

Conditions to Avoid: Not Applicable

Incompatibility (Materials to Avoid): strong oxidants

Hazardous Decomposition Products (including combustion products): None Unusual

Hazardous Polymerization: May Occur Will not occur
Conditions to Avoid: Ignition Sources.

7. SPILL, LEAK AND DISPOSAL PROCEDURES:

Spill Response Procedures (including employee protection measures): Wear gloves and protective shoes. Small/large spills should be diked with inert absorbent and collected for disposal.

Preparing Wastes for Disposal (container types, neutralization, etc.): Incineration or disposal to sanitary landfill in accordance with Federal, States and Local regulations.

NOTE: Dispose of all waste in accordance with Federal, States and Local Regulations.

8. SPECIAL HANDLING INFORMATION:

Ventilation and Engineering Controls: This product should be used with plenty of ventilation.

Respiratory Protection (type): Self contained breathing apparatus in high concentration area.

Eye Protection (type): Regular safety goggles with side shields

Gloves (specify material): Chemical resistant gloves

Other Equipment: Use of mechanical dilution ventilation is recommended whenever this product is used in a confined space and heated above ambient temperatures and/or is agitated.

9. USER'S RESPONSIBILITY

The responsibility to provide a safe workplace remains with the user, who should consider the health hazards and safety information contained herein as a guide and develop required precautions for his operation. Then he should instruct his employees about working procedures for a safe work environment.

The information contained herein is to the best of our knowledge and belief accurate. however, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It s the responsibility of the user to comply with all applicable local, state and federal laws and regulations.